



- Large PVC tank breathers protect chemicals in storage or process tanks.
- Handles extreme temperatures and weather conditions.
- Accommodates airflow rates up to 900 cfm.
- Bi-directional airflow.
- Multi-tiered filtration process.
- Water vapor adsorbent.
- Sight glass indicator for easy system monitoring.
- Rebuildable.

Model Number	DC-6-2-12	DC-6-2-18	DC-10-2-18	DC-10-3-30	DC-14-3-30	DC-14-4-36	DC-18-4-36	DC-18-6-44
Height (mm)	30.5	45.7	45.7	76.2	76.2	91.4	91.4	111.8
Diameter (mm)	5.2	15.2	25.4	25.4	35.6	35.6	45.7	45.7
Filtration Area (cm ²)	307.7	307.7	956.3	889.3	1862.1	1781.1	3078.2	2838.7
Amount of Silica gel (kg)	2.722	4.08	12.25	18.14	40.82	44	88.45	94.35
Adsorption Capacity (litres)	0.85	1.80	4.16	7.19	15.14	17.88	29.53	32.93
Max. Flow Rate @1 PSID (cfm)	100	100	100	250	250	500	500	900
Filtration (μ absolute)	3							
Op. Temp. Range	-28.9° to 121°C							
Hydrophilic Agent	Silica Gel							
Connection Size (NPT)	2"	2"	2"	3"	3"	4"	4"	6"